

Northcoast Yacht 125



125' (38.1 m) NORTHCOAST YACHTS

LOA:	125' (38.1 m)	Year:	Mfg-2010 Model-2010
Beam:	25'5" (7.7 m)	Mfg:	NORTHCOAST YACHTS
Draft:	Min 6'3" (1.9 m)	Type:	Motor Yacht
Speed:	22 knots		Raised Pilothouse
Location:	Seattle, WA, United States	Price:	22,222,000 USD

Additional Specifications For Northcoast Yacht 125:

LOA:	125' (38.1 m)	Year:	Mfg-2010 Model-2010
Mfg. Length:		Mfg:	NORTHCOAST YACHTS
LWL:	110' (33.5 m)	Model:	Raised Pilothouse
Beam:	25'5" (7.7 m)	Type:	Motor Yacht
Draft:	Min 6'3" (1.9 m)		Raised Pilothouse
Hull Mtrl:	Composite	Top:	With Flybridge
Hull Cnfg.:	Semi-Displacement		Hardtop
Hull Designer:	NCY/Frederickson	Cockpit:	No
Deck Mtrl:	Composite	Speed:	22 knots
Disp:		Engines:	2xCaterpillar
Range:			C32
Fuel Cap:	7800 g (29523 l)		1925 HP
Water Cap:	1000 g (3785 l)	Engines Year:	
Holding Tank:	375 g (1419 l)	Staterooms:	5
Flag:	USA	Sleeps:	11
Classifications:	NONE	Heads:	6
Class Type:		Crew Quarters:	3
MCA:		Crew Berths:	5
ISM:		Crew Heads:	3
Location:	Seattle, WA, United States	Captain Cabin:	Yes
		Price:	22,222,000 USD

125' Northcoast Overview

Just launched! This stylish 125' Northcoast motoryacht was just launched and is based in Seattle until she sells. Northcoast is well known and respected for their quality construction and stylish design. There is no need to wait years for delivery on this 5 stateroom yacht.

125' Northcoast Audio And Visual Equipment

Fly Bridge:

2 x Speakercraft CRS8Three Speakers

Fly Bridge Forward:

2 x Speakercraft CRS8Three Speakers

Pilot House:

2 x Speakercraft CRS8Three Speakers

Aft Deck:

2 x Speakercraft CRS8Three Speakers

Curtis Stokes & Associates, Inc.

1323 SE 17th Street Suite 168 Fort Lauderdale, Florida 33316 United States
Contact: Curtis Stokes, Phone: +1.954.684.0218, Email: curtis@curtisstokes.net
URL: <http://www.curtisstokes.net/>

Northcoast Yacht 125

4/3/2010

Page 2

Salon:

50" Pioneer Elite Pro1150HD Plasma Television

10" Martin Logan Dynamo Subwoofer

4 x Speakercraft CRS8Three ASM86630 Speakers

2 x Vienna Acoustic wall mount speaker with silk tweeter and woofers

Salon LEC

Denon DVD-1940 CIBLA Single disc player

Sonance IPort FS-3 on-desk ipod dock with IR control capability

Electrical Room (Cave)

B&K AVR507, dolby digital THX EX dual-zone AV receiver

2 x B&K CT600, 12 channel, 6 zone receiver with internal am/fm tuner

Denon AVR-2802C1 a/v receiver with dolby digital surround EX hdmi

DirecTV DTVD10 basic directv tuner, dedicated music

DirecTV DTVD10 basic directv tuner, galley receiver

DirecTV DTVHDVR21, Direct TV hddvr, Master stateroom

DirecTV DTVHDVR21, Direct TV hddvr, Salon receiver

Speakercraft IRE-3.0, single IR emitter

2x Speakercraft SAC1.0, IR combiner

Zinwell WB616 satellite multiswitch

Galley:

Samsung 23" HD LCD TV

2 x Speakercraft CRS8Three ASM86630 Speakers

Master Stateroom:

42" Pioneer Elite plasma television

Customer Supplied TV Lift, INCA Lift

Definitive Tech. Supercubell Ultra Compact sub

5 x Speakercraft CRS8Three ASM86630 Speakers

Master StateroomLEC

Denon Ipod dock for denon receiver

Denon DVD player, single disk

2 x Speakercraft IRE-3.0

Crew Settee:

Denon DVD-1740, DVD player

DirecTV DTVHDVR21, Direct TV hddvr

2 x GEFEN EXT-COMPAUD-143 audio distribution amplifier

19" Samsung LCD HDTV

2 x Speakercraft CRSTWO speaker with silk tweeter and woofer

1 x Speakercraft IRC-1.1 Mini receiver

Crew Berth 1 & 2:

19" Samsung LCD HDTV, each cabin

Captain's Quarters:

19" Samsung LCD HDTV

Denon DVD-1740, DVD player

DirecTV DTVHDVR21, Direct TV hddvr, Captain's quarters receiver

2 x Speakercraft CRSTWO speaker with silk tweeter and woofer

Dining Area:

2 x Speakercraft CRS8Three ASM86630 Speakers

Starboard Aft Stateroom:

19" Samsung LCD HDTV with atsc tuner

Denon DVD-1740, DVD player

DirecTV DTVHDVR21, Direct TV hddvr

2 x Speakercraft CRSTWO speaker with silk tweeter and woofer

Port Aft Stateroom:

19" Samsung LCD HDTV with atsc tuner

Denon DVD-1740, DVD player

DirecTV DTVHDVR21, Direct TV hddvr

2 x Speakercraft CRSTWO speaker with silk tweeter and woofer

Starboard Forward Stateroom:

23" Samsung LCD HDTV

Denon DVD-1740, DVD player

DirecTV DTVHDVR21, Direct TV hddvr

2 x Speakercraft CRSTWO speaker with silk tweeter and woofer

Port Forward Stateroom:

23" Samsung LCD HDTV

Denon DVD-1740, DVD player

DirecTV DTVHDVR21, Direct TV hddvr

2 x Speakercraft CRSTWO speaker with silk tweeter and woofer

125' Northcoast Deck Equipment

Fenders - 6 x "Polyform" F7 18"X 24" fenders

Docking Lines - 4 x 40'; 2 x 60'; 2 x 20' Nylon braid lines with spliced eye's

Boat Hook - 1 x 8-12ft. Boat Hook

Boarding Ladder - Marquipt 7 step boarding ladder

Anchoring System (Windlass) Warping Winches

2 x Muir (or equiv.) 4500 lbs. Vertical capstan windlass (hydraulic).

2 x Poole (or equiv.) 395lbs. Anchors (Galvanized) located in the Port/Starboard fabricated stainless

steel anchor pockets w/stem guard.

SS Horn Hauser*/ SS Cleats*

Hauser Cleats; (3) port & (3) starboard

(2) SS cleats located on swim step at each warping winches P/S.

SS Hausers - Fore Deck: (1) Port & (1) Starboard

SS Bollards - Fore Deck: (1) Port & (1) Starboard

SS Anti-Chafing Strips - Located at each cleat (when applicable)

Boat Deck

Davit - Nautical Structures (or equiv.) 2500 lb capacity, 270 degree power rotation, w/ handheld control unit.

Tender/Water Toys - After sale owner supplied

Tender/Water Toys Lifting/ Tie Downs - After sale owner supplied

Deck Points (tie down) - SS plate points fastened to the deck in grid pattern.

Chocks (tender) - After sale owner supplied

Hot Tub - Acrylic six person unit TBD

BBQ - Viking BBQ model VGBQ300-2RT (or equiv.)

Sink - Kohler (or equiv.) TBD

Faucet/Lav. Set - Kohler (or equiv.) TBD

Icemarker - "Uline" Model #B12015 (or equiv.)

Fridge - "Uline" Model #75R (or equiv.)

Storage - Under sun pad, port side bar cabinets.

Flybridge

Helm Chairs – 2 x Stidd (or equiv.) TBD

Settee – 2 x Custom FRP application w/ custom storage.

Dining Table – 2 x Corian top w/ custom table base.

Flybridge Door - SS/ Glass weathertight locking single sliding door.

Storage - Under Settee P/S, wing station

AFT Deck

Aft Settee & Table - FRP settee with teak table top & SS/teak fixed base.

Bar - FRP application with Corian (or equiv.) solid surface. Built to accommodate icemaker, fridge and sink.

Sink - Corian (or equiv.)

Faucet/ Lav. Set - Kohler (or equiv.) TBD

Icemaker - "Uline" model #B12015 (or equiv.)

Fridge - "Uline" model #75R (or equiv.)

Storage - Starboard storage in bar cabinets, under settee, port bulwarks locker.

Fire Hydrant – 1 x Fire Hydrant w/ remote start/stop (two total located throughout vessel) c/w 1 1/2" 50ft. fire hose.

Fore Deck

Sun Pad - FRP molded sun pad

Hooks – 6 x SS hooks installed in trunk locker

Storage - Trunk locker, access through gull wing doors P/S TBD

125' Northcoast Electrical System

Wiring - 120/208 VAC three phase & 24 volt DC shop's services power wiring to be marine grade standard wire. Wire and cable runs to be fully supported and neatly arranged. All wiring and cables passing through watertight bulkheads will maintain watertight integrity. Where required, conduits to be routed through FRP pipe and cable trays.

120/208 Volt System (three phase)

24 Volt DC System - Ships DC systems, emergency lighting, selected electronics, navigation equipment, and Trace (or equiv.) inverters are supplied by the "house bank". The main engines and generators are started from two "start" battery banks. One bank will serve port generator and port engine. Second bank will serve starboard generator and starboard engine.

12 volt DC System- Selected electronics & navigation instruments via 24 volt to 12 volt converter.

Shore Power System - Atlas (or equiv.) 75 KVA shore power system.

Distribution Panels - AC distribution: Square D (or equiv.) breaker panels. DC distribution: Custom manufactured.

Shore Power Connections (inc. Glendinning)

100 Amp Power Connections: (4) Hard Connections (2 port & 2 Stbd.) All shore power cords and equipment shall be North American standard 120/208 VAC type as selected by CCY.

Cable TV: (1) located port & (1) located starboard

Telephone: (2) located port & (2) located starboard

Power Cords:

4 x 100' 100 amp cords (3 phase)

1 x 100' telephone cable

1 x 100' TV cable

All shore power cords and equipment shall be North American standard 120/208 VAC type.

Batteries:

House: 12X2 volt cells for 24 volts total

Starboard: 2X12 volt 8D type batteries for 24 volt total
Port Starting: 2X12 volt 8D type batteries for 24 volt total
Emergency Radio: 1X12 volt type 27- gel battery
Battery Changing (inverters/charging)
House: 2 X Trace Inverter/Chargers SW 4024 (or equiv.)
Port/Starboard Starting: 1 X Newmar triple output 3 stage charge process charger model # PT-24-20 (or equiv.)
Emergency Radio: 1 X Statpower 10i (or equiv.) battery charger

Computer Receptacle(s) - Wireless Networking TBD

Ship's Monitoring/ Status

Krill Electronics (or equiv.) A 56 point mixed analog and digital system for the monitoring of key systems and tankage. A graphic display panel with LED indicators is located in the Pilot House as well as LCD touch screen displays in the Engine Room and Crew Area.

Engine Alarms and Indicators – Krill/Caterpillar Electronic Control

Tanks Monitoring - Krill Electronics (or equiv.)

Security Alarm - Ademco Vista Model #20SECN (or equiv.)

Fire Alarm System

UL listed commercial fire alarm panel by Mircom (or equiv.) with pull stations in the Pilot House and Crew Areas and smoke detectors and/or heat detectors in each room/area of the boat.

125' Northcoast Accomodations

MAIN DECK

The Main Deck features a large aft sitting and dining area complete with bar, sink, ice maker and

refrigerator. A full glass aft doorway opens up into an elegant foyer that leads to an expandable

dining space. An expansive interior is created by wide lateral windows, open furniture arrangement and a 9 foot high ceiling in the mid-lounge area. The lounge features a 60 inch media

center, wrap-around seating, ample storage and state of the art stereo surround sound.

To the port

is a day head and entry to the galley. The galley is fully equipped with Wolfe, Sub Zero and GE

appliances and features generous storage and surface space. To the starboard is an accessible

electrical/AV house and entry to the master state room. The master state room has a unique design

that opens to a lowered bath that is lit by an overhead skylight.

LOWER DECK

The Lower Deck is accessible from a staircase that begins on the starboard side of the main deck

and finishes in the middle of the guest space. Forward are two guest cabins each with queen beds and large bathrooms. The center area features two washer/dryers to the port and a fridge/freezer to the starboard. Aft are two guest cabins, the port with a queen size bed and the starboard with two twin beds and a Pullman berth. Both aft cabins have ensuite bathrooms. The aft portion of the lower deck is complete with 3 crew cabins, crew lounge, washer/dryer and small galley. To the starboard are two double berth cabins with a shared bathroom and one queen berth cabin with an ensuite bath on the port side. The engine room is accessible through the crew area and lies midship.

PILOT HOUSE

The raised pilot house features the latest in navigational equipment and is designed with adjustable flat screen monitors that will fold down flush to offer a wide smooth consol. The abundant seating area along the aft of the pilot house features a unique design with an adjustable chase lounge to the starboard side.

SUN DECK

The sundeck is accessible from the pilot house and from an aft staircase the leads up from the main deck. The forward section of the sundeck has a control station that is flanked on either side with generous wraparound seating. The mid section features a large Jacuzzi to the starboard and a bar to the port complete with BBQ, sink, ice maker and refrigerator. Aft of the Jacuzzi and bar lies two low sunpads. To the far aft of the sundeck sits the Tender.

125' Northcoast Galley

Main Galley:

Sub Zero 48" side-by-side

Wolfe 30" wall oven

Wolfe 36" induction cook top

GE Monogram 24" convection microwave

ASKO 24" dishwasher

Sub Zero 24" under counter wine storage

Franke faucet

GE Monogram 15" trash compactor

Aft Deck:

Outdoor 24" undercounter refrigerator
Ice Maker 15"
Sun Deck:
Outdoor 24" undercounter refrigerator
Ice Maker 15"
Built-in 36" BBQ with rotisserie
Crew Mess:
24" undercounter Fridge/Freezer combo

125' Northcoast General Features

General Features

Exterior Rails - 1.5" diameter polished rails with 1.25" stanchions fabricated from 316SS. 2.5" polished 316SS removable hoop rails at swimstep.

Bell Tower - 316SS tube fabrication with 12" chrome bell (PERKO or equiv)

Exterior Deck Surface-All exterior walking decks and stair tread surfaces covered with teak decking.

Windshield Wiper/Washer System-5 pane wipers (IMTRA-EXALTO or equiv.) Single station control in pilothouse and 5 pane freshwater washers.

Windows-Frameless bonded windows, tempered glass w/grey tint. Size thickness as required per classification society.

Portlights-PACIFIC COAST MARINE 316SS in FRP integral recess.

Boarding Stairs-NAUTICAL STRUCTURES port and stbd transversely recessed gangplanks extend from hullside pockets amidships. 160° swing forward and aft on dock.

Freeing Ports - Freeing ports located above the maindeck as required by classification society.

Exterior Passage Doors

Side Deckhouse Port and Starboard- Camming weathertight dual axis, slider full glass w/sidelight.

AFT Deckhouse- Weathertight curved salon aft door, slider full glass w/ twin sidelights.

Transom- Aluminum watertight pantograph door.

AFT deck to crew- Aluminum weathertight door with dogging window.

Note: Doors to be factory painted white.

Hatches

Foredeck - aluminum watertight flush hatch w/hidden hinge, teak covered.

Sidedeck - aluminum watertight flush hatch w/hidden hinge, teak covered.

Swimstep - aluminum watertight flush hatch w/hidden hinge, teak covered.

Flybridge - weathertight slider full glass w/seahood.

Boatdeck- weathertight slider w/seahood

Flybridge Windscreen - 0.75" acrylic

Radar Arch & Hardtop - Arch mast multi-level to accommodate all electronics and antennas. Molded fiberglass painted to match.

Aft Deck Overhead - Satin painted white with molded and applied design details.

Side Deck Boarding Gates - FRP Fabrication, (2) bulwark door's P/S hinged with SS butt hinges.

Cap Rails - Molded FRP fabrication with painted finish.

Hull Side Rub Rails

FRP molded and glassed to hull

Sheer, mid guard capped with 1.50" SS half oval.

Lower guard capped with 2.00" SS half oval

Engine Beds - Aluminum weldment over FRP hull stringers.

Engine Room Flooring - Gel coat finish, molded composite FRP diamond tread.

Limber Holes - 1 _" FRP tubing sealed to laminate through the vessel structural longitudinal frames.

Bilges

5 x "Rule" 3700 bilge pumps located vessel to drain each watertight subdivision. All of the vessels bilges will be coated with isophalic gel coat. All bilges suitably lit.

Anchor Locker - Sprayed with isophalic gel coat (grey) self draining through 1 _" FRP pipe with clamshell cover P/S.

Thru-Hulls - Flanged FRP standpipes at integrally bonded to vessel.

Sea Chests

2 x FRP (Engine Room) chests. Each chest is designed to have necessary capacity to operate cooling functions associated with complete systems. The top of each sea chest is 1" acrylic plate. Sea chest strainers are non-corrosive, low maintenance polymer screens.

Piping System Materials

Fresh water-"AQUA PEX" certified tubing.

Black Water- PVC SCH.40 ("Headhunter" system) & "Sealand" flex hose ("Sealand" system)

Grey Water- PVC SCH.40 runs & ABS piping

Chiller Mains- _" insulated "Insultube" 2 _" to 1 _" copper (1" -3/4" "PEX" used when required)

Fuel- "Parker" 221 FR USCG rated fuel hose & 1 _" SS SCH.40 pipe.

Hydraulics- High pressure lines "Parker" #772TC rated at 4000 PSI.

Fire Suppression System- SS SCH. 40 2" pipe.

Bilge Suction Emergency Line- SS SCH. 40 2" pipe.

Bow Thruster - "American Bow Thruster" hydraulically driven, rated @ 57 hp. With 16" diameter. (4 stations)

Stabilizers

"Trac" Zero-speed by American Bow Thruster model #440 Stabilizer units w/ 16sq. ft., reverse-lock, main "touch screen" control in pilothouse & secondary control on flybridge.

Propellers - 2 x Five Blade, manufactured by Michigan (or equiv.) nibral.

Shafts - 4" Diameter Aquamet 22HS

Shaft Logs & Packing Glands

Shaft logs are one piece FRP construction each equipped with dripless, water lubricated, shaft seals inboard and underwater cutlass bearings with cooling water pick-up.

Struts - Constructed of welded 316 SS

Rudders - Each having 11 (approx.) sq. ft. area.

Rudder Stock - Aquamet 22HS 5" Diameter

Main Engine Mounts - CATERPILLER supply rubber engine mounts.

Generator Mounts - Hydro Elastic mounts supplied by engine manufacturer.

Main Engine Exhaust

Marine exhaust muffled underwater exhaust system directed through the hull bottom with a transom by-pass.

Generator Exhaust - Northern Lights combo waterlift muffler and water bypass shedder.

Zinc Anodes - Zinc anodes located on shafts and transom.

Bonding - Main Strap: 1" X 1/8" copper bar

Steering Wheel - Custom wood in P/H

Fills & Vents

Fills: Fuel: (2 P/S) 2" d recessed in deckhouse side

Water: (1) 1 _" deck fill & (1) dock fill

New Oil: (1) 1 _" fill

Gasoline: (1) 1 _" fill

Vents: vents shall be sized and installed per the builder's standards.

125' Northcoast Hull

Hull mold originally developed Jack Sarin Naval Architect, Inc. subsequent structural engineering and laminate detail supplied by Naval Architect/Engineer, Al Horsmon for Crescent Custom Yachts, Inc.

Hull construction is of sandwich composite laminate, using 100% vinylester resin, with multi-axial e-glass over CORE-CELL foam core. Stiffening is designed with a matrix of composite bulkheads and longitudinal girders. Six watertight compartments are incorporated into the design including the collision bulkhead

forward. Structural design based upon American Bureau of Shipping "1990 Guide for Building and Classing Motor Pleasure Yachts."

Through-hull fittings and mechanical fastenings shall be bedded and sealed with polyurethane adhesive/sealant, 3M-5200.

Limbers - framing members (except watertight bulkheads) incorporate limber holes for free drainage to the bilge sumps. Limber holes shall be lined with FRP laminate. Limber holes arranged to limit bilge water accumulating in isolated pockets.

Deck/House - The Deck/House/Pilothouse/Bulkhead structure are designed and constructed to be as lightweight as possible consistent with the required scantlings. Decks, primary structural bulkheads, house sides and house tops laminated with e-glass roving (woven and/or knit) and mat with integral FR stiffeners.

Deck/House core shall be cross-linked PVC (DIVINYCIL or equiv) or linear polymer foam (CORE-CELL A-500 or equiv.) Through-deck and through-house penetrations shall be locally reinforced and penetrated core is closed off by the laminate. Through-laminate mechanical fittings and all fastenings be bedded and sealed with polyurethane adhesive/sealant, 3M-5200 or equal.

Non-Structural Laminates - Exterior laminates which are not related to the basic structures, such as soffits, deck coamings, bulwark liners, and styling features laminated of FRP skins over core.

Finishes - Exposed surfaces hull, decks and superstructure faired and painted with epoxy and linear polyurethane (IMRON or equiv.) Underwater surfaces of the hull bottom receive epoxy barrier coat and three coats bottom paint (INTERLUX or equiv.)

Sound Insulation - All accommodation surfaces (hull, deck, and superstructure) are insulated

for sound and thermal transmission by 1" thick foam with vinyl cover layer. Carpeted floors with 3/8"

sound deadening, loaded under-pad in addition to carpet underlay. Main engines mounted with CATERPILLER supply vibration/isolation pads. Generators equipped with NORTHERN LIGHTS sound enclosures. Generators are double isolated with factory electro-hydrostatic mounts. Engine room is isolated from the remainder of the vessel by soundproofing using multi-layer sound blanket insulation covered with white composite FRP panels. Engine room air trunks per same schedule.

125' Northcoast Engine /Mechanical Equipment

Main Engines - 2 x CATERPILLER C32 ACCERT- 1285 MHP @ 2300RPM (each) Color: White
Engine Controls – 4 x stations located on flybridge center console, P/S wing stations, & pilothouse.

Generators – 2 x Northern Lights rated @ 65 KW (each). Three phase 120/208 VAC @ 1800RPM. Includes Northern Lights ventilated removable sound shields.

Transmissions – ZF 3055 2.5:1 Reduction

Fuel Transfer Pump - 40gph w manual primer
Fuel Sight Gauges – 3 x Located in E/R
Fuel Transfer Manifold - SS Ball valves on welded manifold

Oil Transfer Pump – 2 x "oberdorfer" (or equiv.) _ hp. Pumps for new and old oil (oil change)

Hydraulic System

Main hydraulic system consists of (2) main engine driven hydraulic pumps on transmission. This system provides hydraulics for the vessels bow, anchor winches, davit, stern warping winches, stabilizer, and the hydraulically driven emergency bilge/fire pump. The system includes an electrically driven back-up pump.

Steering System

A three tier system combining a dual station autopilot, a dual station full follow-up steering system and a four station jog (non follow up) steering system. Steering pressure is provided by a dual pump (A.C. & D.C) hydraulic power unit Kobelt (or equiv.)

Fuel Coalescer

3 x Coalescers; model #"Racor" #FBO-14 connected in parallel each with a capability of 30 gpm each.
Fuel Filters - Racor (or equiv.)

Water Maker System – 1 x Sea Recovery "CoralSea" Watermaker providing 2000 Gallons per day.

Fire Suppression System

FM200 Manually activated with release pulls located in the crew area and pilothouse. Auto release via

E/R heat detector.

Fire Bilge Control Station

Application is provided with both and A.C. motor driven pump and a hydraulically driven pump. Flow chart controls make it possible to use either pump as fire or bilge pump simultaneously.

Fire/Bilge Pumps

MP1 5hp. Electric/ (1) MP1 5hp. Hydraulic, with hydrants (2) located on deck. (5) bilge suctions located as per plans.

Air Conditioning System:

DOMETIC or equiv chilled water, reverse cycle system, (17) zones, with 18 ton capacity. (3) Compressors located in E/R. System equipped with soft starts when coming online. (1) 200 CFM

make-up air handler providing fresh air to vessel (located on flybridge)

Air Conditioning Control Panels - DOMETIC or equiv system supplied control panels.

Air Compressor:

Silent Aire model#100/24 120 PSI (or equiv.), dual silent compressors w/ 5 gal. accumulator tank

located in E/R. (3) Air supply outlets, located in engine room, Fore Deck Trunk Locker, and flybridge.

Includes (1) 25' air hose. (1) additional 20 Gal tank located on flybridge for horn.

E/R Air Intakes & Blowers:

Delta T (or equiv.) application using (2) 21" intake blower units with variable frequency drives controlled by engine speed. The system incorporates a four speed manual control and an automatic

variable speed control for unattended cool-down.

Recovery Tanks – 2 x CRS 300 Coolant Recovery System Reservoirs

Vacuum System - Drainvac w/ hepa Filter

Tool Box - "Snap-On" model #KRA4820A located in crew utility.

Fresh Water System:

Fresh Water Pumps - 2 xHeadhunter Mach 5 (or equiv.) 208 V 20 GPM max. UV filter in line with system.

Fresh Water Hose Bibs – 4 x Hot/ 4 x Cold; Chrome plated taps, located; engine room, bow, boat deck, aft deck.

Swim Shower - Located on the swimstep (exact location TBD)

Wash Down Hose – 2 x 50' hose with spray nozzle.

Black Water System:

Owner/Guest Toilets – 5 x Headhunter Royal Flush-gravity fed to mid ship holding tank.

Crew Toilets – 2 x Headhunter Royal Flush- gravity fed to crew holding tank which is bated fed to midship holding tank.

Suction Pump (Overboard Pump Out) - "Edson" # ELB120

Dockside Connection - Connection for dockside suction on port side aft deck.

Grey Water System:

Mid Ship Sump Pump – 2 x "Rule" 3700 pump. Serving grey water system forward of the Engine Room. (upper & lower decks)

AFT Crew Sump Pump - "Rule" 3700 pump. Serving grey water system aft of the Engine Room. (upper & lower decks)

Grey Water Drainage - All Sinks, showers, and air handlers, with the exception of the galley, aft deck and flybridge sinks, drain into (2) separate gray water sumps. The galley sink, flybridge and aft deck bar sinks drain directly overboard.

Air Conditioning System:

Air Conditioning System - Cuisair MCW1925RCN 4 stage 16 ton chiller horizontal chassis.

Exterior Deck Drains:

Exterior Deck Drains - 2" SCH. 40 PVC piping with drains to be placed for sufficient drainage of flybridge, boat deck, and aft deck. Each drain is covered with SS CCY embossed stain plates.

125' Northcoast Remarks

Builder to furnish as-built drawings of mechanicals, electrical and plumbing systems. All purchaser's manuals, warranty cards, and product documentation will be supplied with vessel.

Dock Trials

After launch, the Builder will conduct at his expense a dock trial of sufficient duration during which all the main and auxiliary machinery shall be thoroughly tested. The dock trial will be carried out at the Builder's wharf. A scheduled list of dock trials will be provided to the Purchaser prior to commencement of said trials, which will include but not be limited to the following:

Main Engines

Hose testing of all windows, port lights, hatches, decks, doors, etc.

Tender davit

Safety equipment, including fire fighting equipment and alarms

Steering gear

Ventilation and heating systems

Generators, main and emergency electrical systems

Monitoring and alarms

Anchoring and mooring systems

Bilge and sanitary systems

All deck machinery

Radio, communications and navigation equipment

Galley, domestic equipment and systems

Priming, pumping tests for all pumps and piping systems

HVAC and ventilation systems, functioning of temperature controls, air changes, Balancing of system, etc...

Any defects found during dock trials will be rectified by the Builder. Builder shall furnish competent personnel to obtain necessary data in machinery spaces and on deck and supply necessary additional

testing gauges, thermometers and/or portable instrumentation as required. All working parts of machinery shall meet manufacturer's parameters and show no tendency to overheat.

Sea Trials

NCY to provide sufficient lube oil and fuel for the initial sea trials only. After satisfactory completion of dock trials, the Builder shall conduct sea trials of suitable length during which the operation of the vessel, including all machinery and equipment shall be examined.

ALL SPEEDS, MEASUREMENTS, CAPACITIES, CONSUMPTIONS, ETC. MAY BE APPROXIMATE OR ESTIMATED. SPECIFICATIONS PROVIDED FOR INFORMATION ONLY. DATA WAS OBTAINED FROM SOURCES BELIEVED TO BE RELIABLE AND IS NOT GUARANTEED BY OWNER OR BROKERS. BUYER ASSUMES THE RESPONSIBILITY TO ASCERTAIN THE CORRECTNESS OF ALL DATA CONTAINED HEREIN AND OTHERWISE PROVIDED AND MUST

INSTRUCT HIS AGENT AND SURVEYORS TO CONFIRM ALL DETAILS FOR ACCURACY PRIOR TO PURCHASE. SUBJECT TO PRIOR SALE, PRICE AND INVENTORY CHANGE, OR WITHDRAWAL FROM MARKET WITHOUT NOTICE.

PUBLISH DATE – MARCH 4, 2010

125' Northcoast Safety And Fire Protection

Life Rafts 2 x 10-man Zodiac (or equiv.)

Life Rings 2 x 30" Life Rings w/ yacht name (vinyl decal)

Life Jackets 19 x Adult USCG approved; 4 x Child USCG approved life jackets.

Medical Kit Zee model #166 (or equiv.)

Ship's Horn Kahlenberg T2 model, chrome plated, low profile triple air horn.

Epirb 1 x ACR Sat 2 406 Mhz. (or equiv.) w/hydrostatic release

Flares 6 xUSCG approved hand held flares/ 6 x parachute flares

Fog Horn 1 x Falcon (or equiv.) hand held air horn

Fire Exting 11 x 5lb ABC (or equiv.) fire extinguishers for each crew and guest accommodation

1 x 15lb Co2 extinguisher for engine room (includes mounting brackets)

Nav. Lights "Aqua Signal" 55 Series, 24 volt.; Port/Starboard lights: 112.5 degrees; Stern Light: 135.0

degrees; Mast Light: 225.00 degrees; Anchor Light: 360.0 degrees

Note: Installed as per manufacturer's instructions.

Disclaimer

The Company offers the details of this vessel in good faith but cannot guarantee or warrant the accuracy of this information nor warrant the condition of the vessel. A buyer should instruct his

agents, or his surveyors, to investigate such details as the buyer desires validated. This vessel is offered subject to prior sale, price change, or withdrawal without notice.

Northcoast 125 salon



Northcoast 125 master stateroom



Northcoast 125 layout

